

## SPECIFICATION SHEET



### HPPE BLENDED COOPER PLAITED LINER WHITE PU PALM COATED GLOVES

#### Double Knitted High Strength HPPE

- + Lightweight Elasticized Liner with Excellent Dexterity
- + Hi-Anti static Function with Cut Protection
- + Exceptional Comfortable fit with High Strength
- + Cut Protection in Comfortable

#### Soft PU Palm Finished

- + Provide Secure Grip in Dry and Wet Environments
- + High Protection from Abrasion

### APPLICATIONS

- + Assembling Process of Electronic Component
- + Working with Sharp Metal, Glass, and Ceramic
- + Automobile Industries / Mechanical Assembly
- + Industrial Applicants / Wiring Operations

### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used.

About 5-10 minute cycle time should be employed.  
Tumble dry on low - maximum temperature 140°F(60°C).



#### DIMENSION(mm)

HEM COLOR				
S	M	L	XL	XXL
White	Green	Grey	Yellow	Black
230	240	250	260	270

Tolerance ±5.0mm

#### SURFACE RESISTIVITY

EN 1149-1	$1 \times 10^3 \sim 1 \times 10^5 \Omega$
-----------	---

#### EN388:2016 / ISO 13997

ABRASION	0	1	2	3	4	
CIRCULAR BLADE CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
LINEAR BLADE CUT	A	B	C	D	E	F

#### TECHNICAL DATA

MATERIAL	HPPE/Copper Nylon blended Spandex
KNITTING	13 Gauge
COATING	PU Palm Finished
SIZE	S / M / L / XL / XXL
ORIGIN	South Korea